Order Form | Ceramic Band Heater



Company:	Contact:	Date:
E-mail:	Tel:	Date required:
SPECIFICATIONS		MONTH / DAY / YEAR
MODEL (select)	erating temperature OC OF 315°	9 0 45°
APPLICATION	270°	10 meter 90° Width
DIAMETER WIDTH inches	Quantity 225°	135°
	ual CONNECTION	INSULATION
Vol	Standard Loc. (°)	1/6" 1/8" 1/4" 1/2"
1 1 2 3 3 3 3.	SIOT: SIZE LOCATION	Cut-Out: SIZE LOCATION 1.
ELECTRICAL CONNECTIONS		
Fiberglass Leads; Length ["] Metal Braid (SS); Length ["] Armour Cable (AC); Length ["]	Post Terminals 1/4 - 20 Thread (standard Ceramic Terminal Covers Plug (specify)	Euro Style: vert. Hor. Ground
HEATER CONSTRUCTION	LOCK UP	ADAPTORS & FITTINGS
1-piece Construction Standard 2-piece Construction; Voltage each half Hinged One Time Expandable	Straps Flange Spring Loaded Strap Stainless	Thermocouple Fitting Hinge
Fully Expandable	Welded Barrel Nut	TERMINAL BOX
Gap: Standard 3/8 (dimension) High Temperature Construction (HT950)	Spring Load Barrel Nut Full Width Strap	Standard Low Profile
SPECIAL INSTRUCTIONS:		

suhmi